

VLS Platform Series

Flexibility for Growing Businesses

The VLS 3.60, 4.60 and 6.60 freestanding laser platforms offer increased maximum laser source power levels and larger working areas than the desktop models. In addition, VLS freestanding laser platforms are equipped with Universal's patented Rapid Reconfiguration™ technology, so laser sources can be installed, removed and exchanged in seconds without the use of tools. The increased workspace, power and flexibility of VLS freestanding laser platforms make them a good choice for growing businesses.



Laser Technology Benefits

- ▶ **Software Controlled** - The laser can be controlled by any software with a print function.
- ▶ **Multi-Material** - Process an endless number of materials available today and in the future.
- ▶ **Multi-Process** - Cut, engrave, mark, and produce photo images in one step.
- ▶ **Non Contact** - Modify material without applying any physical force.
- ▶ **On Demand** - Produce everything you need in real time, without waiting for hard tooling.

Uniquely Universal Features

- ▶ **ULR Laser Sources**
Universal's patented air-cooled free-space gas slab lasers produce an excellent quality beam with even power distribution and good near- and far-field characteristics, making them ideal for laser material processing.
- ▶ **Rapid Reconfiguration™ of Lasers**
Laser platforms with Rapid Reconfiguration can be reconfigured with new laser sources in seconds, without tools. This allows you to configure your laser system to suit the task at hand, increasing quality and throughput.
- ▶ **High Power Density Focusing Optics™**
High Power Density Focusing Optics (HPDFO) allow the laser beam to be focused to a much smaller spot, making it possible to engrave smaller text and produce sharper images at tighter tolerances.
- ▶ **Laser Interface+™**
This materials-based driver automatically determines the optimum processing settings for your target material. Just select the material type, enter in the material thickness, and start the laser system.
- ▶ **1-Touch Laser Photo™**
1-Touch Laser Photo is a proprietary software package that makes it quick and easy to produce photographic images on nearly any material.

System Specifications

	VLS3.60	VLS4.60	VLS6.60
▶ Work Surface Area¹	24 x 12 in (610 x 305 mm)	24 x 18 in (610 x 457 mm)	32 x 18 in (813 x 457 mm)
▶ Maximum Part Size²	29 x 17 x 9 in (737 x 432 x 229 mm)	29 x 23 x 9 in (737 x 584 x 229 mm)	37 x 23 x 9 in (940 x 584 x 229 mm)
▶ Dimensions	36 x 38 x 30 in (914 x 965 x 762 mm)	36 x 38 x 36 in (914 x 965 x 914 mm)	44 x 39 x 36 in (1118 x 991 x 914 mm)
▶ Rotary Capacity	Max Diameter 8 in (203 mm)		
▶ Motorized Z Axis Lifting Capacity	40 lbs (18 kg)		
▶ Available Focus Lenses	1.5 in (38 mm)	2.0 in (51 mm) *standard	2.5 in (64 mm) 4.0 in (102 mm)
▶ Laser Platform Interface Panel	Five button keypad		
▶ Operating System Compatibility	Requires a dedicated PC to operate. Compatible with Windows XP/Vista/7 – 32/64 bit		
▶ PC Connection	USB 2.0		
▶ Cabinet Style	Floor-Standing		
▶ Optics Protection	Air Assist Optional		
▶ Laser Options	10, 25, 30, 40, 50, 60 Watts		
▶ Approximate Weight	235 lbs (107 kg)	270 lbs (122 kg)	325 lbs (147 kg)
▶ Power Requirements	110V/10A; 220V-240V/5A		
▶ Exhaust Connection	One 4 in (102 mm) port 250 CFM @ 6 in static pressure (425 m ³ /hr at 1.5 kPa)		Two 4 in (102 mm) ports 500 CFM @ 6 in static pressure (850 m ³ /hr at 1.5 kPa)

USA

7845 E. Paradise Lane
Scottsdale, AZ 85260

+1 480-483-1214
moreinfo@ulsinc.com

Japan

The Yokohama Landmark Tower
15th Fl. 2-2-1-1 Minato Mirai
Nishi-ku Yokohama-shi
Kanagawa-ken 220-8115 JAPAN

+81 45-224-2270
japansales@ulsinc.com

Europe

Lerchenfelder Gürtel 43
1160 Vienna, Austria

+43 1-402-22-50
eurosales@ulsinc.com

UNIVERSAL[®]
LASER SYSTEMS

Learn more at ulsinc.com



CDRH Class 1 safety enclosure for CO₂ laser³. Class 3R for red laser pointer.



¹ Work area varies by speeds and throughput

² Maximum part size defined as used with 1.5 lens

³ CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.

WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.

Manufactured and protected under one or more U.S. Patents: 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; D517,474. Other U.S. and international patents pending.

©2011 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks, and Rapid Reconfiguration, Laser Interface+, 1-Touch Laser Photo, SuperSpeed and High Power Density Focusing Optics (HPDFO) are trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MCO38-110411
CPT REV 0112